

Date:	Approved:
Type:	
Fixture:	
Project:	

4" LED Gimbal Trims LS-RK-4-GR

STANDARD



FEATURES

- Available in 2700k, 3000k, and 4000k color temperatures.*
- Long-life LEDs provide at least 70% of initial lumen output (L_{70}) for 50,000 hours of operation.**
- Provides up to 750 nominal lumens.
- 10 nominal watts.
- Color rendering index (R_a) > 80.
- 120 (50-60Hz) AC voltage is standard.
- Power factor ≥ 0.90 .
- Dimmable down to 10% with most line voltage dimmers.
- Thermoplastic construction.
- Easy installation in new construction or remodel applications. Equipped with torsion springs.
- Compatible with insulated, non-insulated, and air-tight ceilings.
- E26 medium screw-base (Edison) connector comes standard.
- Compatible with BL4ICLED series.
- This device is not intended for use with emergency exits.

WARRANTY & LISTINGS

- cETLus listed for damp locations.
- Energy Star qualified.
- Complies with FCC Part 15, class B.
- 5-year warranty of all electronics and housing.

* Contact factory for other color temperatures and lumen packages.
** L_{70} hours are IES TM-21-11 calculated hours.

ORDERING INFORMATION


Example: LS-RK-4-GR-27K-ECO



COMPATIBLE DIMMERS

MANUFACTURER & SERIES	PART NUMBER
Lutron Maestro C-L	MACL-153MR
Lutron Skylark C-L	SCL-153P
Leviton Sureslide	6674
Lutron	PD-6WCL
Legrand Harmony	HCL453PTCCCV6

DIMENSIONS



Series	Trim Type		Color Temperature (lumen output)	
			27K-ECO	2700K (675 lm)
LS-RK-4	GR	Gimbal	3K-ECO	3000K (675 lm)
			4K-ECO	4500K (750 lm)