

Date:	Approved:
Type:	
Fixture:	
Project:	

5/6" LED Trims LS-RK-56-BW-V2

STANDARD



FEATURES

- Available in 2700k, 3000k, 3500k, 4000k, and 5000k color temperatures.*
- Long-life LEDs provide at least 70% of initial lumen output (L_{70}) for 50,000 hours of operation.**
- Provides up to 860 nominal lumens.
- 12 nominal watts.
- Color rendering index (R_a) > 80.
- 120 (60Hz) AC voltage is standard.
- Power factor > 0.90.
- Dimmable down to 10% with most line voltage dimmers.
- Thermoplastic construction.
- Easy installation in new construction or remodel applications. Equipped with torsion springs.
- Compatible with insulated, non-insulated, and air-tight ceilings.
- E26 medium screw-base (Edison) connector comes standard.
- Compatible with LS9IC series.
- This device is not intended for use with emergency exits.


WARRANTY & LISTINGS

- cETLus listed for wet locations.
- Operating temperatures of -20°C to 40°C (-4°F to 104°F).
- Complies with FCC Part 15, class B.
- Complies with RoHS (Restriction on Hazardous Substances) requirements.
- 5-year warranty of all electronics and housing.

* Contact factory for other color temperatures and lumen packages.
** L_{70} hours are IES TM-21-11 calculated hours.



DIMENSIONS



ORDERING INFORMATION

Example: LS-RK-56-BW-3-ECO-V2

Series	Trim Type		Color Temperature (lumen output)		Accessories (Order Separately)	
	BW	Baffle	27-ECO-V2	3000K (800 lm)	LS56-TRMPLT-ECO-SQ	Square snap trim
LS-RK-LED56	BW	Baffle	3-ECO-V2	3000K (820 lm)	LS6A-TRMPLT-ECO-SPWHT	Specular white snap trim
			35-ECO-V2	3500K (830 lm)	LS56-TRMPLT-ECO-BK	Black snap trim
			4-ECO-V2	4000K (840 lm)	LS56-TRMPLT-ECO-N	Nickle snap trim
			5-ECO-V2	5000K (860 lm)	LS56-TRMPLT-ECO-BZ	Bronze snap trim