LS-L6-FS 6" ARCHITECTURAL SQUARE LED RECESSED DOWNLIGHT





Power	35W Max.			
Input Voltage	120V/277V/120V-277V			
Lumen	2500/3000LM			
Power Factor	PF>0.98			
CRI	80+/90+			
Beam Angle	60°, 90° Optional			
Dimmable	NONE/0 ~ 10v Dimming			
Light Source Brands	Osram, Seoul, Cree, Luminus			
Lifespan	50000Hours			

ORDERING GUIDE / YOUR PRODUCT CODE



DESCRIPTION

Architectural LED luminaire, iron shell spray production, with anti-corrosion shell. Emergency system is available.

Isolated power supply, safe and without flicker.

LED light source using high quality, high lumen and high CRI LED bead.

Square emitting surface, with uniform light distribution, high luminous efficiency. Energy saving, long lifespan even without maintain.

LAMPSHADE

Aluminum fog reflective reflector, high light uniformity. With marbles design mode, the overall height of the size is controlled, smooth appearance, excellent visual effects.

LIGHT SOURCE\ RADIATOR

High light transmittance, strong light diffusion performance, no shadow no glare. Point light source emitting turned into spherical light emitting.

Milky white light transmission rate reach 90% above,

Excellent concealed light source, achieve the best light transmission rate without seeing the LED lamp bead.

Outstanding heat dissipation aluminum material, the temperature is guaranteed to be the touch temperature below.

LOCATING PART

Locating part, easy for installation, will not cause abnormal phenomena such as deformation.


Resolved the problem of product is not centered.

LISTING / WARRANTY ETL listed to US and Canadian standards for

damp location W/Feed through. 5 Years Limited Warranty.



DIMENSIONS



SERIES	INPUT VOLTAGE	BEAM ANGLE	POWER/LUMEN	CCT	DIMMABLE	LED AVAILABLE	FINISH
 LS-L6-FS 6" Architectural LED Downlight 	120V277V	 60° Optional 90° Optional 	 30W 2500LM 35W 3000LM 	○ 2700K○ 3000K	 ○ NONE ○ 0 ~ 10v Dimming 	O Cree O Citizen	WhiteBlack
	O 120-277V			O 4000K	O TRIAC Dimming	O Epistar	O Satin Nickel
				○ 5000K ○ 6000K		 Seoul Osram 	o Gray

* Customized Also Available