


- Available in LED & GU24
- Fade & Rust Resistant Composite Construction with Powder Coated Aluminum Base
- Wall Mount Only
- UL Listed for Wet Locations
- Standard Pack QTY: 6


COMMERCIAL EUROSTYLE



LS111



LS113



RoHS compliant



STYLE #	LIGHT SOURCE	BODY	DIFFUSER	OPTIONS
LS111 LS113	<p>EOS LED 120V AC, 50/60 Hz, HPF, 50,000 HRS L70*, AMBIENT OP TEMP -40°C TO +40°C, 5 YEAR WARRANTY, DIMMABLE, ENERGY STAR</p> <p>LE800 - 13W, 80 CRI W-1140lm 3000K >88 Lumens Per Watt** C-1280lm 4000K</p>	<p>W-White B- Black</p>	<p>POLYCARBONATE F-Frosted</p>	<p>P-Photocell</p>
	<p>MULTI-VOLT LED 120-277V, 50/60 Hz, CONSTANT CURRENT AT 700mA, DRIVER UL CLASS 2, HPF, THERMALLY PROTECTED ARRAY, 50,000 HRS L70* AMBIENT OP TEMP -40°C TO +40°C, 3 YEAR WARRANTY, ENERGY STAR</p> <p>L900 - 11.3W Power Input C-912lm 4000K CRI 74 (TYP) >80 Lumens Per Watt**</p>	<p>W-White B- Black</p>	<p>POLYCARBONATE F-Frosted</p>	<p>N/A</p>
	<p>GU24 BASE, 120V</p> <p>G13-1 X 13W G213- 2 X 13W G18-1 X 18W G26-1 X 27W</p>	<p>W-White B- Black</p>	<p>POLYCARBONATE F-Frosted</p>	<p>P-Photocell L-CFL, 2700K</p>

*DATA PER LM79/LM80/TM21 AVAILABLE UPON REQUEST

**ESTIMATED FROM LED SOURCE



Scan the QR code to the left to access the Energy Star qualified product list.

Fixtures available with custom packaging options, assembled or knocked down. MOQs apply

For more information contact our sales department at 630-889-8100 or visit solutions4lighting.com