


- Available in LED & GU24
- Fade & Rust Resistant Composite Construction with Powder Coated Aluminum Base
- Wall or Ceiling Mount
- UL Listed for Wet Locations
- Standard Pack QTY: 12


COMMERCIAL EUROSTYLE



LS362



HCMT: 5 1/4"



STYLE #	LIGHT SOURCE	BODY	DIFFUSER	OPTIONS	
LS362	EOS LED 120V AC, 50/60 Hz, HPF, 50,000 HRS L70*, AMBIENT OP TEMP -40°C TO +40°C, 5 YEAR WARRANTY, DIMMABLE, ENERGY STAR	W -White B -Black	POLYCARBONATE F -Frosted	P -Photocell	
	LE800 - 13W, 80 CRI >88 Lumens Per Watt**				W -1140lm 3000K C -1280lm 4000K
	LE1200 - 14W, 80 CRI >102 Lumens Per Watt**				W -1430lm 3000K C -1500lm 4000K
	MULTI-VOLT LED 120-277V, 50/60 Hz, CONSTANT CURRENT AT 700mA, DRIVER UL CLASS 2, HPF, THERMALLY PROTECTED ARRAY, 50,000 HRS L70* AMBIENT OP TEMP -40°C TO +40°C, 3 YEAR WARRANTY, ENERGY STAR	W -White B -Black	POLYCARBONATE F -Frosted	N/A	
	L1800 - 22W Power Input CRI 74 (TYP) >82 Lumens Per Watt**				
	GU24 BASE, 120V G13 -1 X 13W G213 - 2 X 13W G18 -1 X 18W G218 - 2 X 18W G26 -1 X 27W	W -White B -Black	POLYCARBONATE F -Frosted	P -Photocell L -CFL, 2700K	



*DATA PER LM79/LM80/TM21 AVAILABLE UPON REQUEST

**ESTIMATED FROM LED SOURCE

Scan the QR code to the left to access the Energy Star qualified product list.

Fixtures available with custom packaging options, assembled or knocked down. MOQs apply

For more information contact our sales department at 630-889-8100 or visit solutions4lighting.com