

- o Available in LED
- o Powder Coated Cast Aluminum
- o Wall or Ceiling Mount
- o Enclosed & Gasketed
- o ETL Listed for Wet Locations (IP65)
- o Standard Pack QTY: 6



STYLE #	LIGHT SOURCE	BODY	DIFFUSER	OPTIONS	
LS371 LS372	EOS LED 120V AC, 50/60 Hz, HPF, 50,000 HRS L70*, AMBIENT OP TEMP -40°C TO +40°C, 5 YEAR WARRANTY, DIMMABLE, ENERGY STAR***	W -White B - Black	POLYCARBONATE W -White	M -Motion Sensor EB -Emergency Backup (options not available with LE2600)	
	LE1200 - 14W, 80 CRI >102 Lumens Per Watt**				W -1430lm 3000K C -1500lm 4000K
	LE1800 - 22W, 80 CRI >88 Lumens Per Watt**				W -1950lm 3000K C -2130lm 4000K
	LE2600 - 32W, 80 CRI >84 Lumens Per Watt**	W -2700lm 3000K C -2750lm 4000K			
	MULTI-VOLT LED 120-277V, 50/60 Hz, CONSTANT CURRENT AT 700mA, DRIVER UL CLASS 2, HPF, THERMALLY PROTECTED ARRAY, 50,000 HRS L70* AMBIENT OP TEMP -40°C TO +40°C, 3 YEAR WARRANTY, ENERGY STAR***	W -White B - Black	POLYCARBONATE W -White	M -Motion Sensor	
	L1800 - 22W Power Input CRI 74 (TYP) >82 Lumens Per Watt**	W -1704lm 3000K C -1824lm 4000K			



*DATA PER LM79/LM80/TM21 & IES FILES AVAILABLE UPON REQUEST **ESTIMATED FROM LED SOURCE
 ***EXCLUDES LE2600 MODELS AND MODELS WITH MOTION SENSOR OR EMERGENCY BACKUP OPTIONS
 Scan the QR code to the left to access the Energy Star qualified product list.

Fixtures available with custom packaging options, assembled or knocked down. MOQs apply

For more information contact our sales department at 630-889-8100 or visit solutions4lighting.com