

- Available in LED, Incandescent & GU24
- Fade & Rust Resistant Composite Construction
- Knockouts for Conduit
- Wall or Ceiling Mount
- UL Listed for Wet Locations



RoHS compliant



STYLE #	LIGHT SOURCE	BODY	DIFFUSER	OPTIONS
LS391 LS395	EOS LED 120V AC, 50/60 Hz, HPF, 50,000 HRS L70*, AMBIENT OP TEMP -40°C TO +40°C, 5 YEAR WARRANTY, DIMMABLE, ENERGY STAR	W -White B - Black	POLYCARBONATE F -Frosted Prismatic W -White	M -Motion Sensor EB -Emergency Backup
	LE800 - 13W, 80 CRI W -1140lm 3000K >88 Lumens Per Watt** C -1280lm 4000K LE1200 - 14W, 80 CRI W -1430lm 3000K >102 Lumens Per Watt** C -1500lm 4000K LE1800 - 22W, 80 CRI W -1950lm 3000K >88 Lumens Per Watt** C -2130lm 4000K			
	MULTI-VOLT LED 120-277V, 50/60 Hz, CONSTANT CURRENT AT 700mA, DRIVER UL CLASS 2, HPF, THERMALLY PROTECTED, 50,000 HRS L70*, AMBIENT OP TEMP -40°C TO +40°C, 3 YEAR WARRANTY, ENERGY STAR	W -White B - Black	POLYCARBONATE F -Frosted Prismatic W -White	M -Motion Sensor EB -Emergency Backup
	L1800 - 22W Power Input W -1704lm 4000K CRI 74 (TYP) C -1824lm 4000K >82 Lumens Per Watt**			
	INCANDESCENT, MEDIUM BASE, 120V I240 -2 X 40W Max	W -White B - Black	POLYCARBONATE F -Frosted Prismatic W -White	LED LAMP, 3 YEAR WARRANTY DIMMABLE, ENERGY STAR LWE -A19/E26, 80CRI, 3000K LCE -A19/E26, 80CRI, 4000K
	GU24 BASE, 120V G13 -1 X 13W G213 -2 X 13W G18 -1 X 18W G218 -2 X 18W			



*DATA PER LM79/LM80/TM21 & IES FILES AVAILABLE UPON REQUEST **ESTIMATED FROM LED SOURCE
 Scan the QR code to the left to access the Energy Star qualified product list.

Fixtures available with custom packaging options, assembled or knocked down. MOQs apply

For more information contact our sales department at 630-889-8100 or visit solutions4lighting.com